



Maximum Performance



UNIMAC.COM

MAXIMIZE SPACE AND TIME.

UniMac's stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.

- Ideal for small OPL settings with limited space
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products
- 66% more wash capacity than typical retail top load washers
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

STACKED WASHER-EXTRACTOR/TUMBLE DRYERS

STACKED WASHER-EXTRACTOR/TUMBLE DRYERS

| SPECIFICATIONS | UST30 | | UST50 | |
|--|---------------------------|----------------------|------------------|-----------------------|
| | WASHER-EXTRACTOR | TUMBLE DRYER | WASHER-EXTRACTOR | TUMBLE DRYER |
| Control Option | Quantum Standard | | Quantum Standard | |
| Capacity - lb (kg) | 30 (13) x 2 | | 50 (23) x 2 | |
| Overall Width - in (mm) | 31.4 (797) | | 34.4 (875) | |
| Overall Depth - in (mm) | 45.5 (1152) | | 51.3 (1302) | |
| Overall Height - in (mm) | 79.7 (2023) | | 84.3 (2141) | |
| Cylinder Diameter - in (mm) | 24.0 (610) | 30.0 (762) | 26.3 (668) | 33.0 (838) |
| Cylinder Depth - in (mm) | 16.0 (406) | 26.0 (660) | 20.3 (515) | 30.0 (762) |
| Cylinder Volume - cu ft (liters) | 4.2 (119) | 10.6 (300) | 6.3 (178) | 14.8 (419) |
| Reversing Cylinder | - | Standard | - | Standard |
| Door Opening Size - in (mm) | 14.3 (363) | 22.6 (574) | 16.3 (414) | 26.9 (683) |
| Door Bottom to Floor - in (mm) | 14.0 (356) | 51.3 (1303) | 14.6 (370) | 52.3 (1328) |
| Water Inlet Connection - in (mm) | 2 x 0.75 (19) | - | 2 x 0.75 (19) | - |
| Drain Diameter - in (mm) | 1 x 3 (76) | - | 1 x 3 (76) | - |
| Drain Center Height to Floor - in (mm) | 4.3 (108) | - | 4.5 (115) | - |
| Heat Input Power - Btu/hr (kW, Mi/hr.) | - | 73,000 (21.4, 77.0) | - | 95,000 (27.8, 100) |
| Gas Connection - in | - | 1/2 NPT | - | 1/2 NPT |
| Air Outlet - in (mm) | - | 8.0 (200) Elliptical | - | 10.0 (250) Elliptical |
| Airflow - cfm (l/sec) | - | 400 (190) | - | 600 (285) |
| Motor - HP (kW) | Fan | - | 0.5 (0.4) | - |
| | Drive | 1 (0.75) | 0.3 (0.2) | 2 (1.5) |
| Total # of Speeds | 6 | - | 6 | - |
| Cylinder Speeds - RPM (G-Force) | Gentle | 34 (0.4) | - | 33 (0.4) |
| | Wash | 48 (0.8) | - | 46 (0.8) |
| | Distribution | 86 (2.5) | - | 82 (2.5) |
| | Very Low | 282 (27) | - | 269 (27) |
| | Low | 485 (80) | - | 464 (80) |
| | Medium | 542 (100) | - | 518 (100) |
| Electric Specs - amps | B 100-120V/50/60/1 | 15 | 15 | - |
| | X 200-240V/50/60/3 | 15 | 10 | 10 |
| | P 380-415V/50/60/3 | 15 | 10 | 10 |
| Shipping Dimensions - in (mm) | Width | 34.5 (876) | | 35.5 (902) |
| | Depth | 47.0 (1194) | | 54.0 (1372) |
| | Height | 83.0 (2108) | | 89.0 (2261) |
| Net Weight - lb (kg) | 770 (349) | | 910 (413) | |
| Shipping Weight - lb (kg) | 787 (357) | | 930 (422) | |
| Agency Approvals | UL _{us} | | CSA | UL _{us} CSA |

TO LEARN MORE, VISIT UNIMAC.COM OR CALL 1.800.587.5458. ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

Authorized Distributor



RJ Kool Company
800-345-4551
sales@rjkool.com
www.rjkool.com